



VPS

PRODUCT INFORMATION

- ✓ OIML-R76 and EC Class III Type Approved
- ✓ All Stainless Steel Housing, Platform and Pillar Sealed Indicator (IP67 indicator)
- ✓ Wash Down Design According to IP65
- ✓ Food grade stainless steel to meet the toughest food requirements
- ✓ 5 1/2 x 25mm Wide Angle LCD (Backlight)
- ✓ User Programmable Capacity and Division
- ✓ Flexible Platform Collocation
- ✓ Wash Down Version: Aluminum Load Cell and Ionized Load Receiving Structure
- ✓ Fully stainless steel housing, weighing pan, indicator and pillar, ionized load receiving structure and aluminium load cell
- ✓ Protection devices against overload and shock
- ✓ Power ON Zero Tracking, Re-zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, Auto Tare, Accumulation Memory and Dual Interval Selection Functions
- ✓ Complete with Low Battery and Charging Status Indicator
- ✓ Adjustable Feet, Rechargeable Battery, Bubble Level, Power Adaptor and Indicator Dust Cover Included
- ✓ Pan size: 280 x 330 mm
- ✓ Options available: RS-232 Interface



MODEL	CAPACITY	READABILITY
VPS-6	3 / 6 kg	1 / 2 g
VPS-15	6 / 15 kg	2 / 5 g
VPS-30	15 / 30 kg	5 / 10 g

