



▲ SUS304 stainless steel structure



▲ Aluminium load cell with a protective capsule(IP67)



▲ SUS304 L shape pillar

VFSIII

PRODUCT INFORMATION

- ✓ Erosion proof design with heavy-duty rugged construction (IP67) erosion proof or washdown
- ✓ Aluminium load cell with a protective capsule (IP7)
- ✓ 1.5 mm SUS304 food grade stainless steel platter (425 x 525 mm)
- ✓ Stainless steel food grade load receiving structures
- ✓ L shape SUS 304 food grade stainless steel pillar
- ✓ VFS OIML approved stainless steel indicator (IP67)
- ✓ Waterproof cable connector (IP67)
- ✓ Protection devices against overload and shock
- ✓ Power ON Zero Tracking, Re-Zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, low battery signal, Auto Tare, and Accumulation Memory
- ✓ 1/3 Max -e tare range for OIML applications/Full tare range(subtractive) for non-OIML
- ✓ Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- ✓ 5 1/2 x 51mm Bold Type Wide Angle LCD Digits
- ✓ Long battery operation time: 200 hours plus
- ✓ Adjustable Feet, Rechargeable Battery, Power Adaptor, Bubble Level Included
- ✓ Platter size: 425 x 525 mm
- ✓ Options available: Waterproof RS-232 interface



| Model | Capacity | OIML Readability |
|------------|--------------|------------------|
| VFSIII-60 | 30 / 60 kg | 10 / 20 g |
| VFSIII-150 | 60 / 150 kg | 20 / 50 g |
| VFSIII-300 | 150 / 300 kg | 50 / 100 g |

