



# VOP

## CARATERISTICAS

- ✓ OIML R76:2006 Approved in Compliance with EN45501:2015 and NAWI directive 2014/31/EU
- ✓ High Speed 24 bits Multiplexed Delta-Sigma A/D Converters for Performance and Stability
- ✓ Support Unit Price Base as per kg or per 100g
- ✓ Wide Angle LCD Display with LED Backlight
- ✓ Compact Design for Space Efficiency
- ✓ Overload and Shock Protection Mechanism Protects against Excessive Loads and Shock
- ✓ Easy Grip Design for Mobility Convenience
- ✓ Functions Including: Power On Zero Tracking, Manual Zero, Full Subtractive Tare, Fixed Unit Price, Auto Power Saving, Low Battery Warning and Charging Status Indicator, Auto Power Saving, Low Battery Warning and Charging Status Indicator
- ✓ Backlight and Dual Side Display included
- ✓ Rechargeable Battery, Power Adaptor, Adjustable Feet
- ✓ Long Battery Operation Time: 200 Hours Plus
- ✓ Platter size: 225 x 320 mm
- ✓ Options available: RS-232 interface



MODELO	ALCANÇE	DIVISÃO
VOP-3	1.5 / 3 kg	0.5 / 1 g
VOP-6	3 / 6 kg	1 / 2 g
VOP-15	6 / 15 kg	2 / 5 g
VOP-30	15 / 30 kg	5 / 10 g

