



VOC

PRODUCT INFORMATION

- ✓ High speed 24 bits multiplexed Delta-Sigma A/D converters for performance and stability
- ✓ High resolution 30,000 divisions
- ✓ Wide angle LCD display with LED backlight
- ✓ Compact design for space efficiency
- ✓ Overload and shock protection mechanism protects against excessive loads and shock
- ✓ Easy grip design for mobility convenience
- ✓ User friendly functions including: auto piece weight enhancement, full range tare, memory accumulation for weight & total count, overweight / total piece alarm, negative sampling & counting, user selectable automatic / manual tare, user configurable single / dual interval
- ✓ Zero Indicator, Net Weight Indicator, Low Battery Indicator
- ✓ Completed with power on zero tracking, manual zero, full subtractive tare, non-weigh article, auto power saving, low battery warning and charging status indicator
- ✓ Optional dual side display
- ✓ Rechargeable battery, power adaptor, adjustable feet
- ✓ Long battery operation time: 200 hours plus
- ✓ Platter size: 225 x 320 mm
- ✓ Options available: RS-232 interface



MODEL	CAPACITY	READABILITY
VOC-3	3 kg	0.1 g
VOC-6	6 kg	0.2 g
VOC-15	15 kg	0.5 g
VOC-30	30 kg	1 g

