



# VPSII-B

## PRODUCT INFORMATION

- ✓ OIML-R76 and EC Class III Type Approved
- ✓ All Stainless Steel Housing, Platform and Pillar Sealed Indicator
- ✓ Wash Down Design According to IP67
- ✓ Food grade stainless steel to meet the toughest food requirements
- ✓ 5 1/2 x 25mm Wide Angle LCD (Backlight)
- ✓ User Programmable Capacity and Division
- ✓ Flexible Platform Collocation
- ✓ Fully stainless steel construction
- ✓ Erosion Proof Version: Stainless Steel Load Cell and Aluminum Alloy Load Receiving Structure
- ✓ Simple and durable design allows thorough cleaning and corrosion resistance
- ✓ Protection devices against overload and shock
- ✓ Power ON Zero Tracking, Re-zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, Auto Tare, Accumulation Memory and Dual Interval Selection Functions
- ✓ Complete with Low Battery and Charging Status Indicator
- ✓ Adjustable Feet, Rechargeable Battery, Bubble Level, Power Adaptor and Indicator Dust Cover Included
- ✓ Pan size: 330 x 450 mm
- ✓ Options available: RS-232 Interface



MODEL	CAPACITY	READABILITY
VPSII-B30	10 / 30 kg	5 / 10 g
VPSII-B60	20 / 60 kg	10 / 20 g

