



ADW-E II

PRODUCT INFORMATION

- ✓ OIML Class III version, default setting as Dual interval.
- ✓ Higher weighing precision possible for internal use.
- ✓ IP68 rated construction, ideal in damp environments.
- ✓ Moisture-repellent silicone coating that protects the electronics
- ✓ IR sensor for hands-free operation of tare, zero or M+, efficient and hygienic.
- ✓ Durable mechanical keys.
- ✓ Smart Lock offers three different modes for versatile applications.
- ✓ Advanced tare options, continuous, automatic and packaging options.
- ✓ 20mm large LED display digits with progress bar and audible buzzer feedback.
- ✓ Weighing stability filter, Check weighing (Low-OK-High) I.C.W. 18 LEDs.
- ✓ Automatic calibration and gravity settings
- ✓ Built-in real-time clock (RTC), ideal for data output.
- ✓ Overload and shock protection mechanism for the load cell.
- ✓ Power source: AC100~240 V, DC 12V / 0.5A, built-in rechargeable battery: DC6V 4Ah
- ✓ Operating temperature: -10°C / 40°C (14°F / 104°F), R.H. 85%
- ✓ Options: RS-232 - Wi-Fi - Bluetooth
- ✓ Platter size: 215 x 250 mm



| MODEL | CAPACITY | READABILITY |
|----------|----------|-------------|
| ADW-E II | 1,5/3 kg | 0,5/1 g |
| ADW-E II | 3/6 kg | 1/2 g |
| ADW-E II | 6/15 kg | 2/5 g |
| ADW-E II | 15/30 kg | 5/10 g |

