



# AXM-II

## PRODUCT INFORMATION

- ✓ OIML Class III type approved, Dual-Interval set as standard.
- ✓ Hands-Free IR Sensor for tare, zero, or M+ functions, efficient and hygienic.
- ✓ Durable Tact Switch Keypad.
- ✓ Smart Lock offering three distinct modes for versatile applications.
- ✓ Advanced tare options, continuous, auto, and packing options.
- ✓ 3 color 31mm large LCD display with audible buzzer feedback.
- ✓ Adaptive Filtering: advanced filter and display update rate settings.
- ✓ Automatic calibration and gravity settings
- ✓ Real-Time Clock (RTC) built-in real-time clock, ideal for record keeping.
- ✓ Load Cell Protection, built-in overload and shock protection mechanisms.
- ✓ Power Source: AC100~240 V, DC 12V / 0.5A, Internal rechargeable battery: DC6V 4Ah
- ✓ Operating Temperature: -10°C / 40°C (14°F / 104°F), R.H. 85%
- ✓ Options: RS-232 - Wi-Fi – Bluetooth
- ✓ Platter size: 215 x 250 mm



MODEL	CAPACITY	READABILITY
AXM-II	1,5/3 kg	0,5/1 g
AXM-II	3/6 kg	1/2 g
AXM-II	6/15 kg	2/5 g
AXM-II	15/30 kg	5/10 g

